

PF8+ MKII


PF8+ MKII is a passive crossover full range speaker widely used in fixed installation such as multi-functional hall, museum, house of worship, commercial announcements, etc.

PF8+ MKII adopts customized HF driver with 1.75" voice coil, composite membrane and unique driver protection circuit, and customized 8" LF driver with 2" voice coil. The drivers are with advanced cooling system.


HF horn is made of DMF composite material to ensure very warm and dynamic sound. The coverage angle is ($H^\circ \times V^\circ$) $80^\circ \times 70^\circ$ and the horn is 90° rotatable. This ensures accurate coverage no matter in vertical or horizontal direction.

15 years experienced Smart crossover technology, American Benelec XPP audio capacitor, iron-core inductor, customized metal resistor and manually soldered fiber board ensure stability and consistency and zero consumption, even with very high dynamic sound pressure.

The cabinet is made of CNC made Russian birch plywood, and is tongue and groove assembly.



Dimension(W×H×D): 256×424×274mm



FEATURES

- Customized driver
- American Benelec XPP audio capacitor with stable quality, reliable performance
- Manually soldered fiber board to ensure zero consumption even in very high dynamic
- Unique driver protection circuit and high-efficient cooling system of the driver
- DMF composite material HF horn design, coverage angle 90° rotatable
- Solid CNC cabinet made of original Russian birch plywood, exquisite outlook and waterproof enclosure
- Tongue and groove assembly, compact and seamless CNC cabinet design ensures low resonance



SYSTEM CONFIGURATION

- PRO series amplifier
- EA5 series subwoofer


SPECIFICATION

Type	Passive crossover full range speaker
Frequency Response (-6dB anechoic chamber)	60Hz-20KHz
Rated Power (AES)	200W
Maximum Calculated SPL/1M(Continuous/Peak)	118dB/124dB
Horizontal Coverage Angle (Symmetrical)	80°
Vertical Coverage Angle (Symmetrical)	70°
LF Driver	Customized driver, 2" voice coil, 200W(AES)
HF Driver	Customized driver, 1" exit, 1.75" voice coil, 50W(AES)
Crossover Point	2000Hz
Impedance	$8\Omega(+1, -1)$
1 Way Amplifier	2pcs maximum, 4 Ω
Hanging Hardwares	M8 screw
Pole Mount	Base hole $\phi 35\text{mm}$
Input Connectors	2×Speaker connector
Cabinet Material	Russian birch plywood CNC made
Cabinet Color	Black is standard and default color. Consult with Audiocenter sales team for other customized colors
Dimension (W×H×D)	256×424×274mm
Net Weight	11.5Kg


ACCESSORIES




M8 eyebolt
Bearing 200KG




M8 safety bracket
Bearing 130KG




Φ3 steel wire
The wire is 3mm diameter, 1M long with wire ear and wire jacket, bearing 60KG




Single point hanging frame
(PF8*MKII & PF10*MKII90/PF10*MKII60 & PF12*MKII90/PF12*MKII60)
Bearing 80KG



Wall mounting frame(PF8*MKII)
Bearing 40KG




Flexible wall mounting frame
(PF8*MKII & PF10*MKII90/PF10*MKII60 & PF12*MKII90/PF12*MKII60)
Bearing 40KG




Horizontal U bracket
(PF10*MKII90/PF10*MKII60 & PF12*MKII90/PF12*MKII60 & PF15*MKII90/PF15*MKII60)
Bearing 60KG




Coupling bar
Bearing 50KG



Three-foot stand
Bearing 80KG



Flightcase(customized)
For 2 cabinets, with 100mm wheels



Rain bag(customized)

INSTALLATIONS

