


# K-LA218-DSP

K-LA218-DSP, an active DSP-controlled Dual 18" subwoofer, is designed to meet the high requirements of touring performance, rental and fixed installation.

The LF drivers of K-LA218-DSP are two customized 18"drivers (4"voice coil).

User Selectable 3 low-pass filters (80Hz,100Hz,120Hz) in K-LA218-DSP are available for the users to choose according to different environments and music styles.

K-LA218-DSP is a perfect match for all Audiocenter full range loudspeakers, extending band width of frequency response and delivering powerful, impressive, punchy bass sound.



Dimension(WxHxD): 1080x595x760mm

## **FEATURES**

- Hi end digital controller on board (DSP) with 96kHz signal sampling frequency
- Sleep mode automatically if without signal input for 15mins
- Class D amplifier
- Advanced cooling system in the driver
- Rock solid humidity free birch plywood CNC made cabinet
- Comprehensive accessories suitable for different applications
















# **SYSTEM CONFIGURATION**

■ K-LA, K-LA-DSP Series line array

## **ACCESSORIES**





Rain bag(customized)

Wheel







**Flightcase** For 1 cabinet, with 100mm wheels



## **SPECIFICATION**

Frequency Response(-10dB) Maximum Calculated SPL/1M(Continuous/Peak)

LF Driver DSP Processor

Presets

**AMPLIFIER Amplifier Circuitry** Power(RMS standards)

Peak Power Frequency Response

(1W 8Ω 2ch)

Intermodulation Distortion **Total Harmonic Distortion** 

Cooling

Signal Input

Power Input

Signal Output

Protection

Active DSP-controlled subwoofer

32Hz-150Hz 134dB/140dB

Customized 2x18" driver, 4.0"voice coil

96kHz signal sampling frequency 80Hz,100Hz,120Hz

Class D 2800W 5600W

20Hz-20kHz(±0.5dB)

< 0.05% < 0.05% Cooling with fans

DC protection, short circuit protection, overheat protection, input overload protection, output overload protection, soft startup protection, overvoltage protection, undervoltage protection

Female XLR Male XLR Power connector

Power Output AC Power Operating Range

Power consumption (1/8 output power)

CABINET Cabinet Material

Cabinet Color

Grille

Handles Pole Mount Speaker Dimension(W×H×D) Carton Dimensions (WxHxD)

Net Weight Shipping Weight 100V-130V~ or 220V-240V~(±10%,50/60Hz) 295W

Russian birch plywood CNC made Black is the default color. Contact Audiocenter for customization

Iron mesh 8 side

M20 base Φ35mm 1080×595×760mm 846×1186×681mm

101.0kg 105.0kg