

PRO9.0



Output power (1kHz, THD+N =1%)	2×1000W @8Ω stereo 2×1500W @4Ω stereo 2×1950W @2Ω stereo 3000W @8Ω bridge 3900W @4Ω bridge
A-Guard Protection System	DC protection / Short circuit protection / Smart overheat management / Overheat protection / Input overload protection / Output overload protection / Soft startup protection / Limiter protection
Working mode	Stereo/Parallel/Bridge
High Pass Low Pass Low Cut	160Hz, -3dB 160Hz, -3dB 30Hz
LOW FREQ ENHANCED	100Hz
Input Connectors Output Connectors	Female XLR+TRS Speakon 4Pin + binding posts
Input Impedance	Balanced ≥20kΩ / Unbalanced ≥10kΩ
Maximum input voltage	≥20dBu
Sensitivity	0.775V / 36dB / 32dB
Frequency Response (1W 8Ω stereo)	20Hz-20kHz(±0.5dB)
Crosstalk(1kHz, Rated power 8Ω,A weighted)	≥65dB
S/N Ratio (Rated power 8Ω, A weighted)	≥108dB
Damping Factor (1kHz&8Ω)	≥650
Intermodulation Distortion (60Hz:7kHz=4:1,half power)	≤0.05%
THD+N (1kHz,8Ω half power,A weighted)	≤0.05%
Output Circuitry	Class H ⁺
Power Supply	110V~/230V~(±10%,50/60Hz)
Power Consumption (1/8 output power 4Ω)	1050W
Rack Space	3U
Cooling	Back to front venting, mandatory cooling
Dimension (W×H×D)	483×132×510mm
Net Weight	34.0kg



PRO18.0



Output power (1kHz, THD+N =1%)	2×1700W @8Ω stereo 2×2500W @4Ω stereo 2×3000W @2Ω stereo 5000W @8Ω bridge 6000W @4Ω bridge
A-Guard Protection System	DC protection / Short circuit protection / Smart overheat management / Overheat protection / Input overload protection / Output overload protection / Soft startup protection / Limiter protection
Working mode	Stereo/Parallel/Bridge
High Pass Low Pass Low Cut	160Hz, -3dB 160Hz, -3dB 30Hz
LOW FREQ ENHANCED	100Hz
Input Connectors Output Connectors	Female XLR+TRS Speakon 4Pin + binding posts
Input Impedance	Balanced ≥20kΩ / Unbalanced ≥10kΩ
Maximum input voltage	≥20dBu
Sensitivity	0.775V / 36dB / 32dB
Frequency Response (1W 8Ω stereo)	20Hz-20kHz(±0.5dB)
Crosstalk(1kHz, Rated power 8Ω,A weighted)	≥65dB
S/N Ratio (Rated power 8Ω, A weighted)	≥108dB
Damping Factor (1kHz&8Ω)	≥650
Intermodulation Distortion (60Hz:7kHz=4:1,half power)	≤0.05%
THD+N (1kHz,8Ω half power,A weighted)	≤0.05%
Output Circuitry	Class H ⁺
Power Supply	110V~/230V~(±10%,50/60Hz)
Power Consumption (1/8 output power 4Ω)	1450W
Rack Space	3U
Cooling	Back to front venting, mandatory cooling
Dimension (W×H×D)	483×132×510mm
Net Weight	39.0kg

