


SA3118






Dimension(W×H×D):520×700×618mm

PRODUCT PROFILE

3 low-pass filters (80Hz, 100Hz, 120Hz) in SA3118 are available to choose according to different venues and music styles. There is also phase switch. All connectors and function buttons are on the back , panel.

SA3118 subwoofer is with 1-way XLR for input and output. Signals can be sent to different speakers for sound distribution.

ACCESSORIES FOR SA3118



Flightcase For 1 cabinet, with 100mm wheels



Rain bag (customized)

Wheel



Dolly (customized)

SPECIFICATION

Туре	Active DSP-controlled Compact Subwoofer
Frequency Response(-10dB) Maximum Calculated SPL/1M(Continuous/Peak)	35Hz-150Hz 128dB/134dB
LF Driver DSP	Customized 1x18" driver, 4.0" voice coil
Processor Presets AMPLIFIER	48kHz signal sampling frequency 80Hz, 100Hz, 120Hz
Amplifier Circuitry Power (RMS standards) Peak Power Frequency Response (1W 8Ω 2ch)	Class D 1000W 2000W 20Hz-20kHz(±0.5dB)
Intermodulation Distortion Total Harmonic Distortion Cooling System Protection	<0.05% <0.05% Cooling with fans, air convection DC protection, short circuit protection, overheat protection, input overload protection, output overload protection, soft startup protection, overvoltage protection, undervoltage protection
Signal Input Signal Output Power Input AC Power Operating Range Power consumption (1/8 output power)	Female XLR Male XLR IEC power connector 100-130V~/220-240V~(±10%,50/60Hz) 120W
CABINET	CNIC mashing dishaward
Cabinet Material Cabinet Color	CNC machined plywood Black is the default color. Contact Audiocenter for customization
Grille Handles Pole Mount Speaker Dimension (WxHxD) Carton Dimension (WxHxD) Net Weight Shipping Weight	Iron mesh 2 side M20 base Ф35mm 520x700x618mm 606x825x704mm 43.0kg 48.0kg

SUGGESTED APPLICATION



SYSTEM CONFIGURATION

SA3 full range loudspeaker or the same type of full range loudspeaker