


SA3218




Dimension(WxHxD):988x520x714mm

PRODUCT PROFILE


3 low-pass filters (80Hz, 100Hz, 120Hz) in SA3218 are available to choose according to different venues and music styles. There is also phase switch. All connectors and function buttons are on the back panel.

SA3218 subwoofer is with 1-way XLR for input and output. Signals can be sent to different speakers for sound distribution.

ACCESSORIES FOR SA3218




Flightcase
For 1 cabinet,
with 100mm wheels



Rain bag
(customized)



Wheel



Dolly
(customized)

SPECIFICATION

Type	Active DSP-controlled Compact Subwoofer
Frequency Response(-10dB)	32Hz-150Hz
Maximum Calculated SPL/1M(Continuous/Peak)	134dB/140dB
LF Driver	Customized 2x18" driver, 4.0" voice coil
DSP	
Processor	48kHz signal sampling frequency
Presets	80Hz, 100Hz, 120Hz
AMPLIFIER	
Amplifier Circuitry	Class D
Power (RMS standards)	2000W
Peak Power	4000W
Frequency Response (1W 8Ω 2ch)	20Hz-20kHz(±0.5dB)
Intermodulation Distortion	<0.05%
Total Harmonic Distortion	<0.05%
Cooling System	
Protection	Cooling with fans, air convection DC protection, short circuit protection, overheat protection, input overload protection, output overload protection, soft startup protection, overvoltage protection, undervoltage protection
Signal Input	Female XLR
Signal Output	Male XLR
Power Input	IEC power connector
AC Power Operating Range	100-130V~/220-240V~(±10%,50/60Hz)
Power consumption (1/8 output power)	237W
CABINET	
Cabinet Material	CNC machined plywood
Cabinet Color	Black is the default color. Contact Audiocenter for customization
Grille	Iron mesh
Handles	4 side
Pole Mount	M20 base Φ35mm
Speaker Dimension (WxHxD)	988x520x714mm
Carton Dimension (WxHxD)	606x1112x800mm
Net Weight	70.0kg
Shipping Weight	75.5kg

SUGGESTED APPLICATION



Multi-functional meeting room



Museum



DJ



Wedding

SYSTEM CONFIGURATION

- SA3 full range loudspeaker or the same type of full range loudspeaker